





PRODUCT CATALOGUE

1800 121 5113 **TOLL FREE HELPLINE**













MCCB

LED LIGHTING SYSTEM WIRES &

SWITCHGEARS

MCB AND DB^Is

HOME APPLIANCES

MOULDED CASE CIRCUIT BREAKERS

SALIENT FEATURES

- Available in SS Enclosure.
- Adjustable thermal setting (80% 100%)
- Suitable for protection of Distribution and Generating System.
- Shunt Release and Undervoltage release.
- Rotary handle with pad lock & door interlock facility.
- Auxiliary contact and alarm contact I C/O or 2 C/O.

CX1 SERIES

MCCB

RANGE & FRAME SIZE

CMS 63	32A	40A	63A	80A	100A
CMS 100	63A	100A	125A	160A	
CMS 250	100A	125A	160A	200A	250A
CMS 400	320A	400A			
CMS 800	630A	800A			







MCCB DP



MCCB TP



MCCB ADJUSTABLE



MCCB MICRO PROCESSOR

LED LIGHTING SYSTEM

ITEM & RANGE

Led Bulb 5W, 8W, 10W, 12W, 15W, 18W and 25W

Led Tube Light 20W Led Concealed Light 5W, 7W

Led Flood Light COB 20W, 30W, 50W, 100W,150W & 200W

SMD 10W, 20W, 30W, 50W, 100W & 200W

LED Street Light COB 50W & 100W SMD 50W & 100W



DRIVER

High Quality isolation driver for optimal performance of the fixture to ensure less hazarded in operation.



LED Bulb



LED TUBELIGHT



LED Concealed



LED FLOOD LIGHT



LED STREET LIGHT

WIRES AND CABLES

SALIENT FEATURES

- · Lead Free
- Environment Friendly
- Twisted (Unilay Design)
- 3 Layer For Triple Protection
- FRLS (Flame Retardant Low Smoke)



RANGE

Single Core 0.50mm 0.75mm 1.00mm 1.50mm 2.50mm 4.00mm 6.00mm 10.00mm 16.00mm 25.00mm 35.00mm 0.50mm 0.75mm 1.00mm 2.50mm 4.00mm 6.00mm 10.00mm 16.00mm 25.00mm 35.00mm Multi-Core 1.50mm Submersible 1.50mm 2.50mm 4.00mm 6.00mm 10.00mm 16.00mm








WIRE Two Core



WIRE THREE CORE



WIRE FOUR CORE



WIRE SUBMERSIBLE

SWITCH GEARS

SALIENT FEATURES

- Strong endurance and resistance to heat (Tropicalised).
- Flag indicator for two stable positions (I-O) & possible switching on a off, on load, thereby fulfilling the roll of switching device.
- All current carrying parts are of special grade E.T.P. Copper and with silver plated.



RANGE

80A 100A 125A On Load Changeover 40A 63A 160A 200A 250A 320A 400A 630A 800A 1000A 1250A 1600A 2000A 2500A 3150A **TPN Main Switch** 32A 63A 100A 200A I6A Off Load Change Over: I6A 32A 63A 100A 200A 320A 400A 630A 800A 1000A 1250A 1600A 2000A 3150A 1000A **Bus Bar** 32A 63A 100A 200A 320A 400A 630A 800A Kit Kat 16A 32A 63A 100A 200A 320A 400A 500A



ON LOAD Change Over



TPN MAIN SWITCH



OFF LOAD CHANGE OVER



BUS BAR



KIT KAT

MCB and DB's

SALIENT FEATURES

- Entire range i.e. SPN, DP, TP, TPN, from 0.5 Amps. to 63 Amps. duly ISI marked as per IS 8828.
- Reboundless contact mechanism prevents sparking/erosion of contacts.
- Superior arc runner based on current-limiting blow-out rapid extinction magnetic system, permits
 exceptionally low let-through energy.
- Designed to withstand up to 25kA short circuit currents.
- Unique self lubricating special plastics components.



RANGE

(All Ampere ranges are available in SP, SPN, DP, TP, TPN & FP)

MCB 0.50A 2A 5A 6A 10A 16A 20A 25A 32A 40A 50A 63A

ISOLATOR 40A 63A 100A (All Ampere ranges are available in DP & FP)

Miniature Change Over 25A 40A 63A 100A

(All Ampere ranges are available in DP & FP {Open Execution & Sheet Enclosure })











MCB SP

ISOLATOR

MINIATURE
CHANGE OVER

DISTRIBUTION BOARD

ACRYLIC
DISTRIBUTION BOARD

HOME APPLIANCES

SALIENT FEATURES

- Overlapped stainless steel tank
- Automatic thermostat controller
- Glass insulation
- Multi functional safety valve
- Dual light indicator

- Copper heating element
- Present thermal cutout
- Power coated metal body
- Lead with moulded 3 pin top



RANGE

Instant Geyser	I Ltr.	3Ltr.			Chetak	15Ltr.	25Ltr.		
Base Line	15Ltr.	25Ltr.	35Ltr.	50Ltr.	G. Line	15Ltr.	25Ltr.	35Ltr.	50Ltr.
Gemini	15Ltr.	25Ltr.	35Ltr.	50Ltr.	Cronica	15Ltr.	25Ltr.	35Ltr.	50Ltr.
Old Coin	15Ltr.	25Ltr.	35Ltr.	50Ltr.	Square	15Ltr.	25Ltr.		
				30Lti .	Galaxy	15Ltr.	25Ltr.		











CRONICA SQUARE

GALAXY

INSTANT GEYSER

CHETAK